Stormwater Green Infrastructure: Evaluation and Performance

Fouad H. Jaber, PhD, PE


Associate Professor and Extension Specialist
Biological and Agricultural Engineering
Texas A&M AgriLife Extension
Dallas Research and Extension Center






Urban vs. Natural

Local Hydrologic Cycle











Eutrophication

- Impacts due to urbanization:
 - Impact to aquatic habitat: Degradation of habitat structure, loss of pool-riffle structure, reduction in base flow, increased stream temperature, and decline in abundance and biodiversity.




Fish kill at Lake Granbury.

Urban BMPs


- Rain gardenbioretention areas
- Porous pavements
- Green roofs
- Rainwater harvesting








Project Location




- Upper Trinity-White Rock Creek Watershed
- Clayey soil with underlying calcareous layer (Blackland Prairie
- Representative of typical urban watershed


BMP Locations




Bioretention Area




Volume Reduction




Load Reduction: Nitrate




Load Reduction: Orthophosphate





Load Reduction: Sediments



Load Reduction: E. coli









Design and Monitoring

- Stalls: 18'x10'
- ISCO samplers with bubbler flow meters
- Runoff quantity and quality is measured






Pervious Concrete Cross Section



Results: Volume



Volume Reduction Rates

	PICP	Pervious Concrete	Grass Pavers	Gravel Pavers
Reduction Rate	71%	74%	78%	93%

Results: Water Quality


	Control (mg)	Grass Pave (mg)	Grass Pave % reduction	ICP (mg)	% reduction
NO3	221.98	857.55	-286%	654.27	-195%
NH4	272.07	173.43	36%	60.64	78%
TKN	2327.54	1760.51	24%	1023.3	56%
Orthophosphate	2.46	12.08	-391%	20.84	-747%
Total Phosphorus	53.66	85.37	-59%	107.87	-101%
TSS	59833.46	9648.71	84%	32306	48%

TSS Reduction in Per Conc: 57%

in Gravel pavers: 48%










Growth Medium







Volume Reduction

				Н		S		SD
	Rainfal			reductio		reductio		Reductio
Event	1	С	Н	n	S	n	SD	n
Date	inches	gals	gals	%	gals	%	gals	%
12/28/12	1.52	13.04	8.67	33.51%	8.40	35.58%	8.62	33.90%
01/10/13	2.61	39.13	25.67	34.40%	23.13	40.89%	28.15	28.06%
02/11/13	0.9	8.40	5.13	38.93%	5.19	38.24%	2.18	74.05%
03/11/13	1.67	19.71	7.02	64.38%	12.51	36.53%	6.31	67.99%
04/01/13	0.84	2.71	0.00	100.00%	0.00	100.00%	0.00	100.00%
04/04/13	0.84	3.51	1.30	62.96%	1.29	63.25%	1.29	63.11%
04/18/13	0.87	6.96	0.70	89.94%	0.00	100.00%	1.18	83.05%
05/16/13	1.96	24.61	5.62	77.16%	2.63	89.31%	7.32	70.26%
05/22/13	0.89	4.25	0.10	97.67%	0.00	0.00%	0.36	91.53%
06/10/13	1.08	7.73	2.42	68.69%	1.18	84.73%	0.67	91.33%
06/17/13	0.67	0.80	0.00	100.00%	0.00	100.00%	0.00	100.00%
07/11/13	0.72	1.72	0.00	100.00%	0.00	100.00%	0.30	82.53%
07/17/13	1.12	9.27	4.07	56.09%	1.60	82.74%	2.86	69.19%
09/21/13	1.93	7.44	5.37	27.82%	1.12	84.95%	2.66	64.25%
10/16/13	1.88	7.26	3.25	55.23%	5.78	20.39%	3.6	50.41%
10/27/13	1.24	5.25	4.43	15.62%	4.25	19.05%	2.83	46.10%
11/05/13	1.08	5.55	2.54	54.23%	0.04	99.28%	2.24	59.64%
11/26/13	1.22	3.89	0.53	86.38%	1	74.29%	0	100.00%
12/21/13	1.42	7.02	4.19	40.31%	4.4	37.32%	6.96	0.85%




Volume Reduction

Event	Rainfal	С	н	H reductio	S	S reductio	S.D.	SD Reductio
Event Date	inches	gals	gals	n %	gals	n %	SD gals	%
05/09/14		Volum		65.39		76.05		75.33
05/12/14		ction f						0/0
06/09/14								
07/03/14	0.82	5	3.4	0.32	0.17	0.97	0.17	0.97
07/17/14	0.89	6.7	1.47	0.78	0.1	0.99	2	0.70
07/31/14	1.01	7.7	6.1	0.21	0.24	0.97	1.18	0.85
08/06/14	0.56	2.7	0	1.00	0	1.00	0.29	0.89
08/17/14	0.83	4.7	1.18	0.75	0	1.00	0.29	0.94
10/06/14	1.37	15.8	5.54	0.65	2.47	0.84	4.1	0.74
10/13/14	1.54	22	11.9	0.46	8.7	0.60	9.3	0.58
10/13/14	1.54	22	11.9	0.46	8.7	0.60	9.3	0.58
11/05/14	1.13	9.02	0.17	0.98	0.35	0.96	0.29	0.97
11/23/14	0.51	2.5	0	1.00	0	1.00	0	1.00
12/23/14	0.53	3.89	0.59	0.85	0.35	0.91	0	1.00
01/12/15	0.63	4.5	0.66	0.85	2.4	0.47	0.94	0.79
01/23/15	1.17	7.58	3.56	0.53	3.63	0.52	3.28	0.57
02/02/15	0.72	35.7	25	0.30	1.12	0.97	0	1.00
02/25/15	2.22	15.58	8.63	0.45	1.36	0.91	5.66	0.64
03/06/15	1.1	2.36	0	1.00	1.35	0.43	0.17	0.93


Nitrate Loads








Orthophosphate Loads






TSS Loads




Rainwater Harvesting


- Demonstration Component
 - Four cisterns (300, 500, 1500, and 2500 gallon) that serve AgriLife Buildings
 - Storage and outflow measured
 - Serves a drip irrigation system
- Experimental Component
 - 4 roof shelters, represent residential roofs, 55 gallon tanks(3/plot)
 - Turf lawn associated with each, drip irrigation
 - 4 Treatments- Soil moisture, Evapotranspiration, Home owner (rain water), Control: Home owner (city water)
 - Inflow, outflow, water quality

Experimental plot layout







Runoff from time based




Runoff from ET-based



Water Savings from RWH



Water Savings Soil Moisture



Acknowledgements

- This research was made possible by a CWA 319 (h) NPS grant provided by USEPA and TCEQ
- Texas AgriLife Research for providing funds and the location for the constructed BMPs.
- Modeling studies funded by Texas Sea Grant, USEPA, TCEQ and the City of League City, TX



Fouad H. Jaber, PhD, PE

Associate Professor and Extension Specialist

Biological and Agricultural Engineering
Texas A&M AgriLife Extension

Dallas Research and Extension Center f-jaber@tamu.edu

972-952-9672



www.facebook.com/agrilifeecoeng/